

TD330

TFT POS

Customer Display



Flat Screen and Slim Design fits all POS Terminal perfectly!

New Generation Customer Display! EPSON DM-D30 Compatible!

- Clear to read + High Contrast + Ultra Brightness
- Multilanguage Support including English, Chinese, Japanese, Arabic....
- All Range interface: USB (5V only) / RS232 / Ethernet / Wi-Fi / Blue Tooth
- All Command Support including Epson Command and Logic Control.
- USB / OPOS / JPOS driver support is standard.
- Display Mode: 2x20 / 2x10



Compact Design fits Front-Paper-Exit Printer, great space saver!



TD330 Customer Display

Specification

General	Display Method	TFT LCD
	Resolution	480(W) × 3 (RGB) × 272(H) Pixel Dots
	Display Mode	Alphanumeric: 20 digits × 2 lines / Kanji: 10 digits × 2 lines
	Display Color	64K color
	Character Dot Matrix	24x48 dots for 2x20 ; 48x48 dots for 2x10
	Dot Size	0.35 (W) x 0.6 (H) mm
	Viewing Direction	12 O'clock
	Brightness	250 cd/m2
	Character type	Alphanumeric and Compound (2-Bytes) Words
	Character size	10 (H) mm x 6 (W) mm
	User Define Character	128 characters
	Viewing Area	95(W) × 54(H) mm
	Module Kit Dimension	132 (W) x 82 (H) x 22 (D) mm
	Product Dimension	132 (W) x 82 (H) x 22 (D) mm
	Viewing Angle	θL Φ=180°(9 o'clock) 70 degree θR Φ=0°(3 o'clock) 70 degree θT Φ=90°(12 o'clock) 50 degree θB Φ=270°(6 o'clock) 70 degree
	Vertical Rotation	17° ~ 87°
	Net Weight	Approx. 78 grams
Gross Weight	Approx. 430 grams	
Chassis Color	Black or White	
Commands Mode	Ultimate (Incl. EPSON POS Command), LD220, LD540, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Language	[Compound (2-Bytes) Words] Traditional Chinese, Simplified Chinese, Japanese, Korean, Arabic, Persian [Alphanumeric] US English, Int'l English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish...	
Interface	RS-232 (serial) / USB in 5V only / Ethernet / Blue Tooth / Wi-Fi	
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5V - 400mA 12V - 220mA
Safety	EMC standards Safety standards	FCC, CE

Note: Product Manufacturer reserves the right to modify specifications without notification of the contractual partner.



<http://www.labau.com.tw> E-Mail: service@labau.com.tw
 9F., #531-1 Chung Cheng Rd., Hsin Tien District, New Taipei City, 23148 Taiwan, R.O.C.
 Tel: +886-2-2218-2277 Fax: +886-2-2218-5522