

# TD650

6.63" Colorful TFT  
Customer Display



## Multi-Language & Image file support!

### All POS Line Display Command Compatible


Stand-alone type / 2x20 in English



display pattern and display ground and font color could be set by physical button



Slim design with Flat Bezel-less window



2x20 in Spanish



3x30 in Germany+French



4x15 in Chinese

- Supports All command modes included EPSON and Logic Control command.
- Eco Friendly with Low Power Design
- Support Multi-Language included Chinese / Arabic / Persian...
- Resolution: 480(H)x120(V)
- Support Images included JPEG/BMP/PNG/TIF/GIF Files.
- Brightness: 400 Nits with super wide Viewing Angle.
- Display Pattern: 2x20 / 3x30 / 4x30
- OPOS/JPOS driver is standard.



# TD650 Customer Display

## Specification

<b>General</b>	Display Method	TFT LCD
	Resolution	480(H) (x3RGB) x 120(V) pixel
	Display Pattern	<b>Half width (Alphanumeric):</b> 2x20 / 3x30 / 4x30 <b>Full width (Compound Words):</b> 2x20 / 3x15 / 4x15
	Brightness	400 cd/m <sup>2</sup>
	Character type	95 Alphanumeric, 32 International Characters
	Character size	<b>Half width (Alphanumeric):</b> 2x20@ 8.14(W) x 17.18(H) mm 3x30@ 5.09(W) x 10.74(H) mm 4x30@ 5.09(W) x 10.74(H) mm <b>Full width (Compound Words):</b> 2x20@ 8.14(W) x 17.18(H) mm 3x15@ 10.17(W) x 10.74(H) mm 4x15@ 10.17(W) x 10.74(H) mm
	Dot Size (X * Y)	0.339 x 0.358 mm
	Viewing Area	162.72 (W) x 42.96 (D) mm
	Panel Dimension	172 (W) x 58 (D) x 3.5 (H) mm
	Pole Dimension	Per support: 130(L) x 34.5(Dia) mm
	Base Dimension	160(W) x 100(D) x 60(H) mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
	<b>Command Mode</b>	ULTIMATE, EPSON, LD540, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
<b>Language</b>	Traditional Chinese, Simplified Chinese, Korean, Arabic, Turkish, Persian, US English, Int'l English, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish...	
<b>Interface</b>	RS-232 (serial) / USB / BlueTooth (3.0 / 4.0 Dual Mode)	
<b>Connection</b>	Baud rate	Direct connection 9600 or 19,200 bps
<b>Reliability</b>	MTBF	30,000 hours
<b>Power</b>	Consumption	5 VDC
<b>Safety</b>	EMC standards Safety standards	FCC, CE