



## CPC-2101

### 21.5" Intel® Celeron® Processor Processor Fanless PCAP Touch Panel PC

- > Intel® Celeron® Processor N3160 (2M Cache, up to 2.24 GHz)
- > 21.5" LCD 1920x1080 FHD Display with PCAP touch
- > 2 x 204-pin DDR3L 1600 MHz SO-DIMM supports up to 8GB Max (Default: 1 x 4GB DDR3L)
- > 1 x 2.5" Storage
- > 4 x USB 3.0, 2 x USB 2.0, 3 x COM
- > 2 x Intel® i211AT Gigabit Ethernet
- > Fanless System & VESA Compliance
- > 12V 7A 84W Adapter

#### + Spec

System	
<b>Processor</b>	Intel® Celeron® Processor N3160 (2M Cache, up to 2.24 GHz)
<b>System Memory</b>	4GB DDR3L SO-DIMM
<b>SBC</b>	EMX-BSWP
Expansion	
<b>Expansion</b>	1 x Mini PCI-e for 802.11B/G/N WiFi Module
Storage	
<b>Storage</b>	1 x 2.5" Storage 1 x Mini PCI-e supports mSATA
I/O	
<b>USB</b>	2 x USB 2.0 4 x USB 3.0
<b>COM Port</b>	2 x RS232 1 x RS232/422/485
<b>HDMI</b>	1 x HDMI
<b>VGA</b>	1 x VGA
Audio	
<b>Chipset</b>	Realtek ALC662
<b>Audio Interface</b>	Mic-In, Line-Out and S/PDIF
<b>Speaker Output</b>	2 x 3W
Ethernet	
<b>Chipset</b>	2 x Intel® i211AT Gigabit Ethernet
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Mechanical & Environmental	
<b>Operating Temp</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temp</b>	-10°C ~ 50°C (14°F ~ 122°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (L x W)</b>	528 x 345 x 62 mm
<b>Weight</b>	9.48 kg
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Black Coverlens
<b>Construction - Rear</b>	White
Power Requirement	
<b>Power Connector</b>	DC Jack
<b>Power Requirement</b>	+12V
<b>Power Mode</b>	ATX
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 84W Adapter (12V @ 7A)
Panel	
<b>LCD Size</b>	21.5", 16:9
<b>Display Type</b>	Full HD
<b>Resolution</b>	1920 x 1080
<b>Luminance</b>	250nits
<b>Contrast ratio</b>	3000
<b>Viewing angle</b>	(H) 178, (V) 178
<b>Backlight</b>	LED
Data Collection	
<b>Camera</b>	1 x 1.0M Pixels Webcam

#### + Ordering

CPC-2101-BSW-A1R  
21.5" Panel PC with Intel® Celeron® Processor N3160 / 4GB DRAM / 84W Adapter

